

Features

Application

- 1 1/2 - 5 ton sizes
- Upflow and horizontal (counterflow capable with kit)
- Sequenced for demand management
- External access to heater circuit breakers

Installation

- 1 Piece design for easier installation
- Multiposition - Upflow/Horizontal Left/Right

Cabinet

- Foil faced insulation
- Painted, heavy-gauge galvanized cabinet
- Filter rack built into every air handler
- High-strength, UV- and heat-resistant plastic drain pan for corrosion resistance
- Microban® antimicrobial built in to drain pan to resist mold and mildew growth and fouling of the drain
- 2% or less air leakage

Components

- Efficient PCS blower motors
- Standard transformer and blower relay
- Field-installed 5-20 kW electric heat kits with easy plug connections
- Built-in indoor time delay for increased efficiency
- Sleeves on distributor tubing to protect tubing

Accessories


- Counterflow kit
- Single point power kit

10-year limited parts warranty available
when applied with a system.
See limited warranty document for details.

**AIREASE™**

Built for life.Yours.

Model Number Guide



Physical

Model	Volts/Hz/Phase	Max. Elec. Heat Available (kW)	Transformer Size & Type	Filter Size (in.)	Refrigerant Connection (IDS)		Florator Piston Size	Weight (lbs.)
					Suction (in.)	Liquid (in.)		
BCS2M18	208-230/60/1	10	40 VA, Class 2	16 X 20	3/4	3/8	53	129
BCS2M24	208-230/60/1	10	40 VA, Class 2	16 X 20	3/4	3/8	59	131
BCS2M30	208-230/60/1	15	40 VA, Class 2	18 X 20	7/8	3/8	67	148
BCS2M36	208-230/60/1	15	40 VA, Class 2	18 X 20	7/8	3/8	73	148
BCS2M37	208-230/60/1	15	40 VA, Class 2	18 X 25	7/8	3/8	73	172
BCS2M42	208-230/60/1	15	40 VA, Class 2	18 X 25	7/8	3/8	80	172
BCS2M48	208-230/60/1	20	40 VA, Class 2	18 X 25	7/8	3/8	84	177
BCS2M60	208-230/60/1	20	40 VA, Class 2	18 X 25	7/8	3/8	93	190

Electrical

Blower Size	Elec. Heating Cap.		Blower Amps		(2) (3) Total Amps per Circuit						Total Unit Amps		Circuit Breaker	
	kW	Btuh			208v			240v					Amps per Stage	
	(1) 240v	(1) 240v	208v	240v	1	2	3	1	2	3	208	240	1	2
18 & 24 (no heat)	0	0	1.5	1.4	-	-	-	-	-	-	1.5	1.4	15	-
18 & 24	5	17,100	1.5	1.4	19.5	-	-	22.2	-	-	19.5	22.2	30	-
18 & 24	7.5	25,600	1.5	1.4	28.6	-	-	32.7	-	-	28.6	32.7	45	-
18 & 24	10	34,100	1.5	1.5	37.6	-	-	43.1	-	-	37.6	43.1	60	-
30 (no heat)	0	0	1.6	1.5	-	-	-	-	-	-	1.6	1.5	15	-
30	5	17,100	1.6	1.5	19.6	-	-	22.3	-	-	19.6	22.3	30	-
30	7.5	25,600	1.6	1.5	28.7	-	-	32.6	-	-	28.7	32.8	45	-
30	10	34,100	1.6	1.5	37.7	-	-	43.2	-	-	37.7	43.2	60	-
30	15	51,200	1.6	1.5	37.7	18.1	-	43.2	20.8	-	55.7	64.0	60	30
36 & 37 (no heat)	0	0	1.8	1.7	-	-	-	-	-	-	1.8	1.7	15	-
36 & 37	5	17,100	1.8	1.7	19.8	-	-	22.5	-	-	19.8	22.5	30	-
36 & 37	7.5	25,600	1.8	1.7	28.9	-	-	33.0	-	-	28.9	33.0	45	-
36 & 37	10	34,100	1.8	1.7	37.9	-	-	43.4	-	-	37.9	43.4	60	-
36 & 37	15	51,200	1.8	1.7	37.9	18.1	-	43.4	20.8	-	56.0	64.2	60	30
42 (no heat)	0	0	1.9	1.8	-	-	-	-	-	-	1.9	1.8	15	-
42	5	17,100	1.9	1.8	20.0	-	-	22.6	-	-	20.0	22.6	30	-
42	7.5	25,600	1.9	1.8	29.0	-	-	33.1	-	-	29.0	33.1	45	-
42	10	34,100	1.9	1.8	38.0	-	-	43.5	-	-	38.0	43.5	60	-
42	15	51,200	1.9	1.8	38.0	18.1	-	43.5	20.8	-	56.1	64.3	60	30
48 (no heat)	0	0	2.6	2.5	-	-	-	-	-	-	2.6	2.5	15	-
48	5	17,100	2.6	2.5	20.7	-	-	23.3	-	-	20.7	23.3	30	-
48	7.5	25,600	2.6	2.5	29.7	-	-	33.8	-	-	29.7	33.8	45	-
48	10	34,100	2.6	2.5	38.7	-	-	44.2	-	-	38.7	44.2	60	-
48	15	51,200	2.6	2.5	38.7	16.1	-	44.2	20.8	-	56.8	65.0	60	30
48	20	68,300	2.6	2.5	38.7	36.1	-	44.2	41.7	-	74.9	85.8	60	60
60 (no heat)	0	0	4.1	3.9	-	-	-	-	-	-	4.1	3.9	15	-
60	5	17,100	4.1	3.9	22.2	-	-	24.7	-	-	22.2	24.7	30	-
60	7.5	25,600	4.1	3.9	31.2	-	-	35.2	-	-	31.2	35.2	45	-
60	10	34,100	4.1	3.9	40.2	-	-	45.6	-	-	40.2	45.6	60	-
60	15	51,200	4.1	3.9	40.2	18.1	-	45.6	20.8	-	58.3	66.4	60	30
60	20	68,300	4.1	3.9	40.2	36.1	-	45.6	41.7	-	76.3	87.2	60	60

(1) For 208 volt use .751 correction factor for kW and Btuh

(2) 15 and 20 kW (2 stage models) require 2 supply circuits

(3) Circuit #1 includes blower motor amps

Blower

Model	Motor Size (hp)	Blower Size (in.)	Speed	CFM @ ESP - in. W.C.				
				0.1	0.2	0.3	0.4	0.5
BCS2M18	1/4	10 x 6	<i>Low* (Red)</i>	720	700	660	610	520
			Med (Blue)	1000	930	840	710	630
			High (Black)	1040	960	870	780	660
BCS2M24	1/4	10 x 6	Low (Red)	720	700	660	610	520
			<i>Med* (Blue)</i>	1000	930	840	710	630
			High (Black)	1040	960	870	780	660
BCS2M30	1/4	10 x 6	Low (Red)	930	920	890	840	740
			<i>Med* (Blue)</i>	1060	1040	1010	950	840
			High (Black)	1290	1270	1210	1150	1040
BCS2M36	1/3	11 x 8	<i>Low* (Red)</i>	1140	1120	1110	1080	1000
			Med (Blue)	1350	1350	1320	1260	1090
			High (Black)	1490	1470	1420	1340	1250
BCS2M37	1/3	11 x 8	<i>Low* (Red)</i>	1140	1120	1110	1080	1000
			Med (Blue)	1350	1350	1320	1260	1090
			High (Black)	1490	1470	1420	1340	1250
BCS2M42	1/2	11 x 8	Low (Red)	1200	1190	1160	1120	1000
			<i>Med* (Blue)</i>	1400	1410	1390	1300	1190
			High (Black)	1540	1530	1510	1390	1250
BCS2M48	1/2	11 x 8	Low (Red)	1590	1580	1530	1440	1320
			<i>Med* (Blue)</i>	1760	1710	1640	1540	1400
			High (Black)	1890	1820	1740	1610	1450
BCS2M60	1/2	11 1/2 x 9	Low (Red)	1780	1750	1670	1550	1390
			<i>Med* (Blue)</i>	2070	1960	1860	1710	1480
			High (Black)	2110	2070	1950	1770	1590

All data given while air handler is operating with a wet DX coil and air filter installed.

Speeds marked in italics with an asterisk * are the factory settings for both heating and cooling.

Cooling speeds should not be reduced below factory settings.

Different speeds can be set for heating mode.

Accessories

Kit Number	Description	Used with
12W61	Counterflow Kit	All BCSs
LB62009C	Single Point Power Kit	All BCSs

Electric Heat Model Number Guide


	A	EH	BCC	05	N	S	A	-	1		
Accessory											Revision Code
Electric Heat											A - 208-230V/60hz/1Ph
Applicable Product Family BC* - Air Handler											Cabinet Size
Heat Size											Circuit Protection
05 - 5 kW Electric											N - None
07 - 7.5 kW Electric											C - Circuit Breaker
10 - 10 kW Electric											
15 - 15 kW Electric											
20 - 20 kW Electric											

Electric Heat Kits

Kit Number	Description	Used on
AEHBCC05NSA-1	5 kW with Terminal Block	BCS2*18, 24, 30, 36, 37, 42, 48, 60
AEHBCC05CSA-1	5 kW with Circuit Breaker	BCS2*18, 24, 30, 36, 37, 42, 48, 60
AEHBCC07NSA-1	7.5 kW with Terminal Block	BCS2*18, 24, 30, 36, 37, 42, 48, 60
AEHBCC07CSA-1	7.5 kW with Circuit Breaker	BCS2*18, 24, 30, 36, 37, 42, 48, 60
AEHBCC10NSA-1	10 kW with Terminal Block	BCS2*18, 24, 30, 36, 37, 42, 48, 60
AEHBCC10CSA-1	10 kW with Circuit Breaker	BCS2*18, 24, 30, 36, 37, 42, 48, 60
AEHBCC15CSA-1	15 kW with Circuit Breaker	BCS2*30, 36, 37, 42, 48, 60
AEHBCC20CSA-1	20 kW with Circuit Breaker	BCS2*48, 60

Dimensions (in.)

Air Handler Size	A (in.)	B (in.)	C (in.)	Supply Duct Opening		Return Duct Opening	
				Depth (in.)	Width (in.)	Depth (in.)	Width (in.)
BCS2M18-24	46 3/4	22	18 1/2	17	16 1/2	20 1/4	16
BCS2M30-36	51	22	21 1/4	17	19 1/4	20 1/4	18 3/4
BCS2M37-48	54	26	21 1/4	21	19 1/4	24 1/4	18 3/4
BCS2M60	60	26	21 1/4	21	19 1/4	24 1/4	18 3/4



AIREASE™

Built for life. Yours.

All specifications and illustrations subject to change without notice and without incurring obligations.

www.airease.com
1-800-448-5872

